

# Heavy-duty general purpose trolley 2 shelves 800×500 mm

Project \_\_\_\_\_

Order \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

|                     |             |
|---------------------|-------------|
| <b>Product code</b> | <b>Type</b> |
| 0112172             | SSW 8x5/2   |

## FUNCTIONAL DESCRIPTION

Serving trolley in heavy version with deep-drawn shelves.



## EQUIPMENT FEATURES

**Hygienic stainless steel surfaces**  
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

**Disk bumpers**  
The elastic plastic rollers on all four corners of the appliance provide reliable protection against damage during transportation. Thanks to their simple design, they can be replaced quickly and without tools, which reduces maintenance costs and increases operational readiness.

**High Manoeuvrability: 4 swivel castors, 2 with total locks**  
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

**Shelves with sound-absorbing mats**  
The sound-absorbing mats supplied effectively reduce the noise level. This creates a quieter atmosphere in the guest area – for greater well-being and comfort.

**Deep-drawn shelf**  
The shelf is deep-drawn and has a closed surface with an all-round profile edge. Dirt and liquids are reliably retained – for quick, thorough cleaning in daily operation.

## GENERAL TECHNICAL DATA

|                       |          |
|-----------------------|----------|
| <b>Width rated</b>    | 800 mm   |
| <b>Depth rated</b>    | 500 mm   |
| <b>Nominal height</b> | 1.015 mm |
| <b>Width actual</b>   | 895 mm   |
| <b>Depth actual</b>   | 595 mm   |

|                      |                 |
|----------------------|-----------------|
| <b>Height</b>        | 1.015 mm        |
| <b>Weight</b>        | 18 kg           |
| <b>Payload</b>       | 120 kg          |
| <b>Main material</b> | Stainless steel |

## INTERIOR PROPERTIES

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| <b>Board construction</b>        | With sound insulation board<br>Welded shelf |
| <b>Number of shelves</b>         | 2                                           |
| <b>Execution of board rim</b>    | Folding<br>Profile edge                     |
| <b>Clearance between shelves</b> | 591 mm                                      |

## MOBILITY

|                                       |                                                  |
|---------------------------------------|--------------------------------------------------|
| <b>Set of castors</b>                 | 2 swivel castors with brakes<br>2 swivel castors |
| <b>Castor attachment</b>              | Bolt-on panel                                    |
| <b>Castor bearing type</b>            | Plain bearing                                    |
| <b>Castor housing material</b>        | Plastic                                          |
| <b>Wheel ø</b>                        | 125 mm                                           |
| <b>Type of tyre tread</b>             | Rubber – Standard                                |
| <b>Wheels with thread guard</b>       | Yes                                              |
| <b>Antistatic wheels</b>              | No                                               |
| <b>Impact protection construction</b> | Deflector rollers                                |
| <b>Push handle construction</b>       | Push bar                                         |