

Platform trolley 800×500 mm

Product code	Type
0112602	PW 8x5

FUNCTIONAL DESCRIPTION

Platform trolley with deep-drawn 31.5 × 19.7" (800 × 500 mm) shelf.

- Robust stainless steel construction ensures long-lasting durability and hygienic use in commercial and medical environments
- Deep-drawn shelf with profile edge and sound insulation provides stable, quiet transport and easy cleaning
- Closed, continuous round tube frame offers sturdy support and integrated one-sided push bar for excellent manoeuvrability
- Four polyethylene disc bumpers protect trolley and surroundings from damage during operation
- Swivel casters with total locks and reinforced mounting plates guarantee smooth movement and secure positioning

EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Disk bumpers
The elastic plastic rollers on all four corners of the appliance provide reliable protection against damage during transportation. Thanks to their simple design, they can be replaced quickly and without tools, which reduces maintenance costs and increases operational readiness.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

GENERAL TECHNICAL DATA

Width rated	800 mm
Depth rated	500 mm
Nominal height	1.017 mm
Width actual	895 mm
Depth actual	595 mm
Height	1.017 mm
Weight	13 kg
Payload	120 kg
Main material	Stainless steel

Project _____

Order _____

Quantity _____

Date _____



INTERIOR PROPERTIES

Board construction	With sound insulation board Welded shelf
Number of shelves	1
Execution of board rim	Folding Profile edge

MOBILITY

Castor equipment	
castor_type	quantity
Swivel castor with lock	2
Swivel castor	2
Castor attachment	Bolt-on panel
Castor bearing type	Plain bearing
Castor housing material	Plastic
Wheel ø	125 mm
Type of tyre tread	Rubber – Standard
Design of the locks	Total lock
Impact protection construction	Deflector rollers
Push handle construction	Push bar