

General purpose trolley ergonomic handle 2 shelves 1000×600 mm

Project _____

Order _____

Quantity _____

Date _____

Product code
0133723

Type
SW 10x6/2 ERGO

FUNCTIONAL DESCRIPTION

Serving trolley in ERGO version with deep-drawn shelves.



EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Disk bumpers
The elastic plastic rollers on all four corners of the appliance provide reliable protection against damage during transportation. Thanks to their simple design, they can be replaced quickly and without tools, which reduces maintenance costs and increases operational readiness.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

Ergonomic handle
Ergonomic handle for a more upright posture and increased legroom while pushing.

Deep-drawn shelf
The shelf is deep-drawn and has a closed surface with an all-round profile edge. Dirt and liquids are reliably retained – for quick, thorough cleaning in daily operation.

Shelves with sound-absorbing mats
The sound-absorbing mats supplied effectively reduce the noise level. This creates a quieter atmosphere in the guest area – for greater well-being and comfort.

GENERAL TECHNICAL DATA

Width rated	1.000 mm
Depth rated	600 mm
Nominal height	1.270 mm
Width actual	1.235 mm
Depth actual	695 mm
Height	1.270 mm
Weight	21 kg
Payload	100 kg
Main material	Stainless steel

INTERIOR PROPERTIES

Board construction	With sound insulation board With reinforcement beam Welded shelf
Number of shelves	2
Execution of board rim	Profile edge
Clearance between shelves	591 mm

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Round pin
Castor bearing type	Plain bearing
Castor housing material	Plastic
Wheel ø	125 mm
Type of tyre tread	Rubber – Standard

General purpose trolley ergonomic handle 2 shelves

Wheels with thread guard	Yes
Antistatic wheels	No
Impact protection construction	Deflector rollers
Push handle construction	ERGO push bar