

Hook trolley 3 pairs of hooks

Project _____

Order _____

Quantity _____

Date _____

Product code	Type
7500032	HAW 605/465/1460 1/3HP

FUNCTIONAL DESCRIPTION

Hook trolley for transport and storage of sterile supplies baskets and other items suitable for being attached to hook trolleys.

- Hygienic stainless steel construction ensures durability and easy cleaning for sterile environments
- Welded hook pairs provide secure attachment for sterile goods baskets, optimising transport and storage
- Four swivel castors with two total locks enable high manoeuvrability and stable positioning
- Disc bumpers protect trolley and surroundings from damage, enhancing longevity
- Robust tubular frame with curved corners offers a self-supporting design for reliable daily use



EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Hooks for sterile goods baskets
The integrated hook system enables the flexible attachment of mesh baskets, sterile supply containers and sterile supply baskets. Maximum flexibility for optimum use of space in sterile processing.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Back hole
Castor bearing material	Galvanised steel
Castor bearing type	Ball bearing
Castor housing material	Steel (galvanised)
Wheel ø	75 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Antistatic wheels	Yes
Impact protection construction	Deflector rollers

GENERAL TECHNICAL DATA

Width actual	605 mm
Depth actual	465 mm
Height	1.460 mm
Weight	6 kg
Payload	180 kg
Main material	Stainless steel

HOOK PROPERTIES

Number of hooks	6
Number of hook pairs	3
Load capacity per hook	30 kg
Hook pitch	400 mm