

Hook trolley 6 pairs of hooks

Product code	Type
7500033	HAW 605/675/1460 2/6HP

FUNCTIONAL DESCRIPTION

Hook trolley for the transport and storage of sterile goods baskets and other accessories for the hook system.

- Hygienic stainless steel surfaces ensure easy cleaning and maintain sterile conditions
- Hooks designed for sterile goods baskets enable secure and organised storage
- High manoeuvrability provided by swivel castors allows effortless transport and precise positioning
- Two castors with total locks guarantee stability during loading and unloading processes
- Robust stainless steel construction offers durability and long service life in demanding environments

EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Hooks for sterile goods baskets
The integrated hook system enables the flexible attachment of mesh baskets, sterile supply containers and sterile supply baskets. Maximum flexibility for optimum use of space in sterile processing.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

GENERAL TECHNICAL DATA

Width actual	605 mm
Depth actual	675 mm
Height	1.460 mm
Weight	7 kg
Payload	300 kg
Main material	Stainless steel

HOOK PROPERTIES

Number of hooks	12
Number of hook pairs	6
Load capacity per hook	30 kg
Hook pitch	400 mm

Project _____

Order _____

Quantity _____

Date _____



MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Back hole
Castor bearing material	Galvanised steel
Castor bearing type	Ball bearing
Castor housing material	Steel (galvanised)
Wheel ø	75 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Antistatic wheels	Yes
Impact protection construction	Deflector rollers