

Hook trolley 4 pairs of hooks

Product code	Type
7500465	HAW 605/675/1097 2/4HP

FUNCTIONAL DESCRIPTION

Hook trolley for the transport and storage of sterile goods baskets and other hanging parts for the hook system.

- Hygienic stainless steel surfaces ensure easy cleaning and maintain high hygiene standards
- Hook rails on both sides maximise storage capacity and facilitate organised transport of sterile goods
- Hooks designed for sterile goods baskets provide secure and efficient handling in medical logistics
- High manoeuvrability with swivel castors and total locks allows smooth movement and stable positioning
- Durable stainless steel construction guarantees long-lasting performance and resistance to wear

EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Hooks for sterile goods baskets
The integrated hook system enables the flexible attachment of mesh baskets, sterile supply containers and sterile supply baskets. Maximum flexibility for optimum use of space in sterile processing.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

Hook rails on both sides
Maximum efficiency in everyday clinical practice thanks to loading on both sides. The hook rails on both sides of the trolley allow optimum use of space for medical products and instruments. More capacity with the same space requirement for maximum efficiency.

GENERAL TECHNICAL DATA

Width actual	605 mm
Depth actual	675 mm
Height	1.097 mm
Weight	6 kg
Payload	240 kg
Main material	Stainless steel

Project _____

Order _____

Quantity _____

Date _____



HOOK PROPERTIES

Number of hooks	8
Number of hook pairs	4
Load capacity per hook	30 kg
Hook pitch	400 mm

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Round pin
Castor bearing material	Galvanised steel
Castor bearing type	Ball bearing
Castor housing material	Plastic
Wheel ø	100 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Antistatic wheels	No
Impact protection construction	Deflector rollers