

# Medidul hook trolley 2x4 pairs of hooks

**Product code**

7500801

**Type**

HAW 650/1005/1657 2/4HP Medidul

## FUNCTIONAL DESCRIPTION

Hook trolley for transport and storage of sterile supplies baskets and other items suitable for being attached to hook trolleys.

- Hygienic stainless steel surfaces ensure easy cleaning and maintain sterile conditions
- Hook rails on both sides provide efficient organization and accessibility of sterile goods baskets
- Welded shelf bolts offer robust construction and long-lasting durability
- Four swivel castors, including two with total locks, deliver high manoeuvrability and secure positioning



## EQUIPMENT FEATURES

### Hygienic stainless steel surfaces

Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

### Hooks for sterile goods baskets

The integrated hook system enables the flexible attachment of mesh baskets, sterile supply containers and sterile supply baskets. Maximum flexibility for optimum use of space in sterile processing.

### High Manoeuvrability: 4 swivel castors, 2 with total locks

Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

### Welded shelf bolts

Welded shelf support bolts are compatible with shelf supports, L-profile rails, U-profile rails and slide-in frames. The flexible system allows tool-free height adjustment or replacement of the support.

### Hook rails on both sides

Maximum efficiency in everyday clinical practice thanks to loading on both sides. The hook rails on both sides of the trolley allow optimum use of space for medical products and instruments. More capacity with the same space requirement for maximum efficiency.

## GENERAL TECHNICAL DATA

|              |          |
|--------------|----------|
| Width actual | 650 mm   |
| Depth actual | 1.005 mm |
| Height       | 1.657 mm |
| Weight       | 14 kg    |
| Payload      | 300 kg   |

Project \_\_\_\_\_

Order \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

### Main material

Stainless steel

## SLIDE-IN PROPERTIES

### Pitch

75 mm

## HOOK PROPERTIES

### Number of hooks

16

### Number of hook pairs

8

### Load capacity per hook

30 kg

### Hook pitch

333 mm

## MOBILITY

### Set of castors

2 swivel castors with brakes  
2 swivel castors

### Castor attachment

Round pin

### Castor bearing type

Ball bearing

### Castor housing material

Plastic

### Castor housing colour

Grey

### Wheel ø

100 mm

### Type of tyre tread

Rubber – Standard

### Wheels with thread guard

Yes

### Antistatic wheels

No

### Impact protection construction

Deflector rollers

# Medidul hook trolley 2×4 pairs of hooks

## SHELVING PROPERTIES

|                      |                    |
|----------------------|--------------------|
| Shelving norm        | Standard 5 Medidul |
| Set including covers | No                 |