

Sterile goods transport cart for 9 STU

Product code	Type
7504646	STW/VV 9StE 1249/754/1464

FUNCTIONAL DESCRIPTION

Transport trolley for transport and storage of sterile supplies in containers or baskets. 160 mm stainless steel castors as standard. With sign holder.

- Closed design with hinged doors ensures safe storage and protects contents from external influences while facilitating hygienic cleaning
- Doors with 2-point locking and transport latch with sealing provide maximum security and prevent unauthorised access
- Height-adjustable solid shelves offer flexible, stable storage surfaces adaptable to various goods
- Welded interior creates seamless, gap-free surfaces for effortless cleaning and highest hygiene standards
- True-tracking mobility with swivel and fixed castors enables precise manoeuvring and operational safety

EQUIPMENT FEATURES

All-round bumper strip at the bottom

The robust all-round bumper strip reliably protects against damage from collisions with trolleys or walls, ensuring your equipment stays intact and your workday safer.

Closed design with hinged doors

The closed design includes an all-round closed construction with hinged doors for easy handling. The design ensures safe storage and protects the inside of the transport trolley from external influences. The smooth surface is free of openings or crevices and facilitates cleaning. The robust stainless steel construction ensures both durability and high standards of hygiene.

True-tracking mobility: 2 swivel castors, 2 fixed castors

2 swivel castors, 2 fixed castors: The trolley stays on track, even under heavy loads. Precise manoeuvring, fewer corrections, greater operational safety.

Doors with 2-point locking

The doors feature a 2-point locking system for maximum security and sealing. The ergonomic closure can be quickly opened with one hand and automatically engages when closing. Ideal for professional use in commercial kitchens and medical facilities.

Stainless steel paper clip

The robust stainless steel paper clip enables hygienic and secure attachment of trolley information. The corrosion-resistant material ensures a long service life even with intensive use.

Transport latch incl. sealing

The innovative locking system reliably protects the contents from unauthorised access and prevents accidental opening while driving. Thanks to the additional seal, it is possible to tell at any time whether the trolley has been opened without authorisation – a decisive advantage for sensitive areas.

Clear status display

The status display in red and green allows employees to quickly identify the status of the transported goods.

Project _____

Order _____

Quantity _____

Date _____



Push bars

Push bars are rods made of stainless steel round tubes attached vertically to the corners of a transport trolley's body. Two-handed gripping at any handle height enables ergonomic, easy manoeuvring of the transport trolley.

Height-adjustable shelves

The tool-free height adjustment allows the shelves to be quickly and easily adapted to different requirements. Ideal for goods of varying heights in commercial kitchens and medical facilities.

Welded interior

The welded interior provides seamless and gap-free surfaces for maximum hygiene. The smooth construction enables effortless cleaning and meets the highest hygiene requirements in commercial kitchens and medical facilities.

Solid shelves

The solid shelves provide a secure and stable storage surface for your goods. Thanks to the smooth surface, they are particularly easy and hygienic to clean – ideal for professional use in catering and medical environments.

GENERAL TECHNICAL DATA

Nominal format	StE baskets 600 × 300 mm
Quantity nominal format	9
Width actual	1.249 mm
Depth actual	754 mm
Height	1.464 mm
Weight	119 kg
Payload	200 kg
Main material	Stainless steel

Sterile goods transport cart for 9 STU

INSERT PROPERTIES

Pitch	61,5 mm
-------	---------

HOUSING PROPERTIES

Cart construction	Fully welded
Cart housing construction	Single-walled
Cover construction	Welded roof with cross-hatch embossing
Number of doors	2
Door construction	Hinged doors
Door lock (closed)	2-point locking Transport latch with sealing tab
Door lock (open)	Extension piece
Max. Door opening angle	270 °
Door seal construction	Lip seal on door

INTERIOR PROPERTIES

Cart interior construction	Seamlessly welded
Board construction	Height-adjustable shelf pitch_61_5 Insertable shelf
Number of shelves	2

MOBILITY

Set of castors	2 fixed castors 2 swivel castors with brakes
Castor attachment	Bolt-on panel
Chassis suitability	Off-premises transport
Castor bearing material	Stainless steel
Castor bearing type	Ball bearing
Castor housing material	Stainless steel
Wheel ø	160 mm
Type of tyre tread	Rubber – Standard
Suitable for transport cart washing devices	Suitable for washing machines
Towing device	Not available
HGV transport securing device	No
Impact protection construction	Bumper strip around the bottom
Push handle construction	Push handles