

Hook trolley set for laminating pouches

Product code	Type
7506513	HAW 605/675/1620 2/8HP Pouch

FUNCTIONAL DESCRIPTION

The Hook trolley set for laminating pouches by Hupfer serves the transport and storage of laminating pouches.

- Hygienic stainless steel surfaces ensure easy cleaning and maintain sterile conditions
- Hook rails on both sides provide versatile storage and efficient organisation of laminating pouches
- Hooks designed for sterile goods baskets enable secure and orderly transport of medical supplies
- High manoeuvrability with swivel castors and total locks allows smooth movement and stable positioning
- Robust stainless steel construction guarantees durability and long-lasting performance in demanding environments

EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Hooks for sterile goods baskets
The integrated hook system enables the flexible attachment of mesh baskets, sterile supply containers and sterile supply baskets. Maximum flexibility for optimum use of space in sterile processing.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

Hook rails on both sides
Maximum efficiency in everyday clinical practice thanks to loading on both sides. The hook rails on both sides of the trolley allow optimum use of space for medical products and instruments. More capacity with the same space requirement for maximum efficiency.

GENERAL TECHNICAL DATA

Width actual	605 mm
Depth actual	675 mm
Height	1.620 mm
Weight	30 kg
Payload	300 kg
Main material	Stainless steel

Project _____

Order _____

Quantity _____

Date _____



HOOK PROPERTIES

Number of hooks	16
Number of hook pairs	8
Load capacity per hook	30 kg
Hook pitch	320 mm

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Back hole
Castor bearing material	Galvanised steel
Castor bearing type	Ball bearing
Castor housing material	Steel (galvanised)
Wheel ø	75 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Antistatic wheels	Yes
Impact protection construction	Deflector rollers